Chemistry. Pure. Efficient.



ZEOflair[™] 340 Technical Datasheet



ZEOflair 340 is a highly active, hydrophobic adsorbent for the removal of undesirable odors, flavors, and VOCs. Due to its three-dimensional open structure, ZEOflair 340 effectively removes a broad range of odor/VOC molecules. This special adsorbent system can be easily incorporated as an additive to existing polymer formulations through a master batch or direct compounding.

ZEOflair 340 is strongly selective for the adsorption of a wide range of odors/VOCs from air, various packaging materials, and formulations, even in high humidity conditions. It can effectively reduce a range of organic and inorganic compounds to ppm levels, even in humid/wet conditions. Potential ZEOflair 340 applications for odor/VOC control include polymer & paper packaging, coatings, adhesives, interior automotive plastics, and recycled post consumer and post industrial plastics.

Typical Properties (all nominal values)	Value	Unit
Average particle size	<7	μm
Appearance, form	white powder	
LOI (loss on ignition), 950°C	<8	wt%
Thermal stability	>800	°C

Additional Information	
Generic Names	Hydrophobic adsorbent, Zeolite
Packaging	Steel drums of 20 kg and Steel drums of 90 kg
Storage	When stored in original sealed packages in a cool, dry condition, the product has a
	shelf life of five years if packaged in drums.
Safety	In accordance with Regulation (EC) No. 1272/2008 (GHS/CLP), the product does not
	need to be classified or labeled.
CAS No	1318-02-1
EINECS No	215-283-8 (930-985-0: REACH associated)
REACH No	01-2119455853-31-xxxx
Customs tariff	2842.10

All information contained in this leaflet is given in good faith but without warranty or guarantee of any kind whatever, whether implied or expressed.